

HMT335 Humidity and Temperature Transmitter

For high temperatures

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	1
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT330	5	0																					PRICE
1 Transmitter type	HMT335																								
2 Cable length	2 m cable 5 m cable 10 m cable 15 m cable																								
3 No additional temperature probe																									
4 Parameters	RH+T RH+T+Td+Tdf+a+x+Tw+ppm+pw+pws+h+dT																								
5 Display	No display Graphical display with keypad																								
6 Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC-power (100...240 VAC) Universal AC-power (100...240 VAC) + US power cord Universal AC-power (100...240 VAC) + EUR power cord Universal AC-power (100...240 VAC) + UK power cord Universal AC-power (100...240 VAC) + AUS power cord External US AC-adapter (for LAN/WLAN interface in USA and Canada) Not IP65																								
7 Signal output	Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) - Ch1&Ch2 are mandatory - Ch3 is optional + Serial interface RS232 or optional communication module	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V																							
8 Analog output signals	No 3rd analog output																								
9 for CH1, CH2 and CH3	RH (0... 100%RH) T (range: see below) Td (-20...+100°C) (-4...+212°F) Tdf (-20...+100°C) (-4...+212°F) a (0...600g/m3) (0...262 grft/3) Tw (0...+100°C) (+32...+212°F) x (0...500g/kg d.a) (0...3500gr/lb) h (-40...+1500 kJ/kg) (-9.5...+652.6 Btu/lb) ppm (0...5000) (0...5000) pw (0...1000 hPa) (0...14.5psi) pws (0...1000 hPa) (0...14.5psi) dT (-10...+50°C) (14...+122°F)																								
SPECIAL Define quantity	Ch1: _____ Ch2: _____ Ch3: _____ Ch1: _____ Ch2: _____ Ch3: _____																								
11 Analog output range for temperature	No temperature output -40...+60°C (-40...+140°F) -40...+80°C (-40...+176°F) -40...+120°C (-40...+248°F) -40...+180°C (-40...+356°F) -20...+60°C (-4...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -20...+180°C (-4...+356°F) 0...+60°C (+32...+140°F) 0...+100°C (+32...+212°F) 0...+120°C (+32...248°F) 0...+180°C (+32...356°F) -60...60°C (-76...+140°F) Special : _____																								
12 Output units	Metric Non-metric																								
13 Option for module slot 1	No module Relay output RS-485 serial interface (galvanically isolated) LAN (Ethernet) interface + 2 m cable (RJ45) WLAN (Wireless Ethernet) interface + antenna Data logger module																								
14 Option for module slot 2	No module Relay output 3rd Analog output Data logger module	Choose also analog output signal for Ch3 Not possible if the data logger module has already been chosen in item 13																							
15 Cable bushings	Cable gland M20 x 1.5 Conduit fitting NPT1/2" 8-pole connector with 5m cable 8-pole counter connector equipped with screw terminals Bushing Set (Cable gland M20 x 1.5 and Conduit fitting NPT1/2")	spare cable: 212142 spare connector: 212416																							
16 Transmitter installation	Normal mounting Wall mounting plate Pole installation kit Pole installation kit with rain shield DIN rail kit	item: 214929 item: 215108 item: 215109 item: 215094																							
17 Humidity sensor type	General purpose and high chemical concentrations with chemical purge function General purpose with chemical purge function	HUMICAP180R spare: HUMICAP180R HUMICAP180RC spare: HUMICAP180RC HUMICAP180 spare: 15778HM HUMICAP180C spare: 229011SP																							
18 Sensor protection	PPS plastic grid & stainless steel netting PPS plastic grid Sintered stainless steel filter Stainless steel grid	spare: DRW010281SP spare: DRW010276SP spare: HM47280SP spare: HM474533SP																							
19 Installation kit for probe	No kit Mounting flange	item: 210696																							
20 Operating manual language	No manual English German French Finnish Swedish pdf user's guides available at: www.vaisala.com/hmt330																								
21 PC Accessories	No Service cable for PC, RS232 (D9 female connector) MITOLINK software for Windows® with RS232 service cable Service cable for PC, USB MITOLINK software for Windows® with USB service cable	item: 194466ZZ item: 215005 item: 219685 item: 219916																							
22 Calibration	ISO9001 compliant factory calibration ISO9001 extended temperature range calibration (-20°C, 0°C, +60°C) Special calibration	service item for calibration: 216989 see separate order form																							
23 Additional maintenance	No maintenance and repair contract																								
																								TOTAL	
																								QTY	
																								TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT330 | 5 | L | 0 | A | 1 | 0 | 1 | B | C | A | B | 1 | 0 | 0 | A | 0 | A | A | B | A | A | 1

End customer: _____

HMT337 Humidity and Temperature Transmitter with warmed probe

For high humidities

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	PRICE
Vaisala HUMICAP® Humidity and Temperature Transmitter HMT330 7																								
1 Transmitter type	HMT337 7																							
2 Cable length (dew point probe)	2 m cable S 5 m cable T 10 m cable U 20 m cable R																							
3 Additional temperature probe	No probe 0 2 m cable 1 5 m cable 2 10 m cable 3 20 m cable 7																							
NOTE: select to measure RH and T																								
4 Parameters	Td+Tdf+pw (dew point probe only) C RH+T+Td+Tdf+pw+ppm+pw+psw+h+dT (with additional T probe) D																							
5 Display	No display 0 Graphical display with keypad 1																							
6 Power supply	10...35 VDC, 24 VAC 0 10...35 VDC, 24 VAC with galvanic isolation 1 Universal AC-power (100...240 VAC) 2 Universal AC-power (100...240 VAC) + US power cord 3 Universal AC-power (100...240 VAC) + EUR power cord 4 Universal AC-power (100...240 VAC) + UK power cord 5 Universal AC-power (100...240 VAC) + AUS power cord 6 External US AC-adaptor (for LAN/WLAN interface in USA and Canada) Not IP65 9																							
7 Signal output	Analog output channel (Ch1&Ch2&Ch3) 4... 20 mA 1 Analog output channel (Ch1&Ch2&Ch3) 0... 20 mA 2 - Ch1&Ch2 are mandatory Analog output channel (Ch1&Ch2&Ch3) 0... 1 V 3 - Ch3 is optional Analog output channel (Ch1&Ch2&Ch3) 0... 5 V 4 Analog output channel (Ch1&Ch2&Ch3) 0... 10 V 5 + Serial interface RS232 or optional communication module																							
8 Analog output signals	No 3rd analog output A																							
9 for Ch1, Ch2 and Ch3	RH (0... 100%RH) B B B T (range: see below) C C C Td (-20...100°C) (-40...+212 F) D D D Tdf (-20...100°C) (-40...+212 F) E E E a (0...600µg/m3) (0...262 grift3) F F F Tw (0...100°C) (+32...+212 F) G G G x (0...500g/kg d.a) (0...3500gr/lb) H H H h (-40...1500 kJ/kg) (-9.5...+652.6 Btu/lb) J J J ppm (0...5000) K K K pw (0...1000 hPa) (0...14.5psi) L L L pws (0...1000 hPa) (0...14.5psi) M M M dT (-10...+50 °C) (14...+122 F) N N N SPECIAL Define quantity Ch1: Ch2: Optional Ch3: X X X Define scale Ch1: Ch2: Optional Ch3:																							
	Channel 1 Channel 2 Channel 3, choose A, if not needed																							
11 Analog output range for temperature	No temperature output A -40...+60°C (-40...+140°F) B -40...+80°C (-40...+176°F) C NOTE: -40...+120°C (-40...+248°F) D -40...+180°C (-40...+356°F) E T output is desired -20...+60°C (-4...+140°F) F -20...+80°C (-4...+176°F) G -20...+120°C (-4...+248°F) H -20...+180°C (-4...+356°F) J 0...+60°C (+32...+140°F) K 0...+100°C (+32...+212°F) L 0...+120°C (+32...+248°F) M 0...+180°C (+32...+356°F) N -60...60°C (-76...+140°F) P Special : X																							
12 Output units	Metric 1 Non-metric 2																							
13 Option for module slot 1	No module 0 Relay output 1 RS-485 serial interface (galvanically isolated) 2 LAN (Ethernet) interface + 2 m cable (RJ45) 4 WLAN (Wireless Ethernet) interface + antenna 5 Data logger module 6																							
14 Option for module slot 2	No module 0 Relay output 1 3rd Analog output Choose also analog output signal for Ch3 3 Data logger module Not possible if the data logger module has already been chosen in item 13 6																							
15 Cable bushings	Cable gland M20 x 1.5 A Conduit fitting NPT1/2" B Note: The Universal C AC power not connected spare cable: 212142 C through 8-pole connector spare connector: 212416 D 8-pole counter connector equipped with screw terminals Bushing Set (Cable gland M20 x 1.5 and Conduit fitting NPT1/2") E																							
16 Transmitter installation	Normal mounting 0 Wall mounting plate item: 214829 1 Pole installation kit item: 215108 2 Pole installation kit with rain shield item: 215109 3 DN rail kit item: 215094 4																							
17 Humidity sensor type	Chemical tolerant composite sensor HUMICAP180RC spare: HUMICAP180RC D Composite sensor with chemical purge HUMICAP180RC spare: HUMICAP180RC E Composite sensor for fuel cell applications HUMICAP180RC spare: HUMICAP180RC F Composite sensor HUMICAP180C spare: 229011SP 5 Composite sensor with chemical purge HUMICAP180C spare: 229011SP 6																							
18 Sensor protection	PPS plastic grid & stainless steel netting spare: DRW010281SP A Sintered stainless steel filter spare: HM47280SP C Stainless steel grid spare: HM47453SP D Membrane SST filter for fuel cell applications spare: 214848SP F Vaporized hydrogen peroxide (VHP) resistant filter spare: 231865 G																							
19 Installation kit for probe	No kit A Duct installation kit (for RH probe) item: 210697 C Swagelok NPT 1/2" item: SWG12NPT12 K Swagelok ISO 3/8" item: SWG12ISO38 L Duct installation kit (RH + T probes) item: 210697+215003 P Swagelok NPT 1/2" + Swagelok NPT 1/8" (RH+T) item: SWG12NPT12+SWG12NPT18 Q Swagelok ISO 3/8" + Swagelok ISO 1/8" (RH+T) item: SWG12ISO38+SWG12ISO18 R Swagelok ISO 1/2" item: SWG12ISO12 Y Splash/direct water protector for warmed RH&T and T probes HMT330WPA 1																							
20 Operating manual language	No manual A English B German C French D Finnish E Swedish F Japanese G Russian H																							
pdf user's guides available at: www.vaisala.com/hmt330																								
21 PC Accessories	No A Service cable for PC, RS232 (D9 female connector) item: 194466ZZ B MITOLINK software for Windows® with RS232 service cable item: 215005 C Service cable for PC, USB item: 219685 D MITOLINK software for Windows® with USB service cable item: 219916 E																							
22 Calibration	ISO9001 compliant factory calibration service item for calibration: 216989 A ISO9001 extended temperature range calibration (-20 °C, 0 °C, +60 °C) N Special calibration see separate order form X																							
23 Additional maintenance	No maintenance and repair contract 1																							
TOTAL																								
QTY																								
TOTAL VALUE																								

Selections in bold are included in the prices of the basic versions.
Selections in *italics* are available at an extra price.

Example of order code with typical settings:

HMT330 | 7 | S | 1 | D | 1 | 0 | 1 | B | C | A | B | 1 | 0 | 0 | A | 0 | D | A | B | A | A | 1

End customer: _____

HMT338 Humidity and Temperature Transmitter

For pressurized pipelines

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT338	8	0																				
1	Transmitter type	HMT338	8																					
2	Cable length	2 m cable for 232 mm probe 5 m cable for 232 mm probe 10 m cable for 232 mm probe 2 m cable for 454 mm probe 5 m cable for 454 mm probe 10 m cable for 454 mm probe 20 m cable for 454 mm probe	V W X 1 2 3 9																					
3	No additional temperature probe		0																					
4	Parameters	RH+T <i>RH+T+Td+Tdf+a+x+Tw+ppm+pw+pws+h+dT</i>	A B																					
5	Display	No display <i>Graphical display with keypad</i>	0 1																					
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC-power (100...240 VAC) Universal AC-power (100...240 VAC) + US power cord Universal AC-power (100...240 VAC) + EUR power cord Universal AC-power (100...240 VAC) + UK power cord Universal AC-power (100...240 VAC) + AUS power cord <i>External US AC-adaptor (for LAN/WLAN interface in USA and Canada) Not IP65</i>	0 1 2 3 4 5 9																					
7	Signal output	Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) <i>+ Serial interface RS232 or optional communication module</i>	4... 20 mA 0... 1 V 0... 5 V 0... 10 V	1 3 4 5																				
8	Analog output signals	No 3rd analog output																						
9	for Ch1, Ch2 and Ch3	RH (0... 100%RH) T (range: see below) Td (-20...+100°C) (-4...+212 °F) Tdf (-20...+100°C) (-4...+212 °F) a (0...600/m3) (0...262 gr/ft3) Tw (0...+100°C) (+32...+212°F) x (0...500g/kg d.a) (0...3500gr/lb) h (-40...+1500 kJ/kg) (-9.5...+652.6 Btu/lb) ppm (0...5000) (0...5000) pw (0...1000 hPa) (0...14.5psia) pws (0...1000 hPa) (0...14.5psia) dT (-10...+50 °C) (14...+122 °F)	B C D E F G H J K L M N X	B B C D E F G H J K L M N X																				
10	SPECIAL Define quantity Define scale	Ch1: _____ Ch2: _____ Optional Ch3: _____ Channel 1 Channel 2 Channel 3, choose A, if not needed	X X X																					
11	Analog output range for temperature	No temperature output -40...+60°C (-40...+140°F) -40...+80°C (-40...+176°F) Note: -40...+120°C (-40...+248°F) -40...+180°C (-40...+356°F) T output is desired -20...+60°C (-4...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -20...+180°C (-4...+356°F) 0...+60°C (+32...+140°F) 0...+100°C (+32...+212°F) 0...+120°C (+32...248°F) 0...+180°C (+32...356°F) -60...60 °C (-76...+140°F) Special :	A B C D E F G H J K L M N P X																					
12	Output units	Metric Non-metric	1 2																					
13	Option for module slot 1	No module Relay output RS-485 serial interface (galvanically isolated) LAN (Ethernet) interface + 2 m cable (RJ45) WLAN (Wireless Ethernet) interface + antenna Data logger module	0 1 2 4 5 6																					
14	Option for module slot 2	No module Relay output 3rd Analog output Choose also analog output signal for Ch3 Data logger module Not possible if the data logger module has already been chosen in item 13	0 1 3 6																					
15	Cable bushings	Cable gland M20 x 1.5 Conduit fitting NPT1/2" Note: The Universal AC power not connected through 8-pole connector! 8-pole connector with 5m cable spare cable: 212142 8-pole counter connector equipped with screw terminals spare connector: 212416 Bushings Set (Cable gland M20 x 1.5 and Conduit fitting NPT1/2")	A B C D G																					
16	Transmitter installation	Normal mounting Wall mounting plate item: 214829 Pole installation kit item: 215108 Pole installation kit with rain shield item: 215109 DIN rail kit item: 215094	0 1 2 3 4																					
17	Humidity sensor type	General purpose and high chemical concentrations HUMICAP180R spare: HUMICAP180R with chemical purge function HUMICAP180RC spare: HUMICAP180RC General purpose HUMICAP180 spare: 15778HM with chemical purge function HUMICAP180C spare: 229011SP	A C 1 4																					
18	Sensor protection	PPS plastic grid & stainless steel netting spare: DRW010281SP PPS plastic grid spare: DRW010276SP Sintered stainless steel filter spare: HM47280SP Stainless steel grid spare: HM474535SP	A B C D																					
19	Installation kit for probe	Ball valve set (ISO 1/2") item: BALLVALVE-1 Pressure fitting NPT 1/2" Pressure fitting ISO 1/2"	M N V																					
20	Operating manual language	No manual English German French Finnish Swedish pdf user's guides available at: www.vaisala.com/hmt330 Japanese Russian	A B C D E F J K																					
21	PC Accessories	No Service cable for PC, RS232 (D9 female connector) item: 194466ZZ M70LINK software for Windows® with RS232 service cable item: 215005 Service cable for PC, USB item: 219685 M70LINK software for Windows® with USB service cable item: 219916	A B C E																					
22	Calibration	ISO9001 compliant factory calibration service item for calibration: 216989 ISO9001 extended temperature range calibration (-20 °C, 0 °C, +60 °C) Special calibration see separate order form	A N X																					
23	Additional maintenance	No maintenance and repair contract	1																					

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT338 8 V 0 A 1 0 1 B C A B 1 0 0 A 0 A A B A A 1

End customer: