



MD 300 SURGE PULSE CURRENT PROBE SET



- **Specially designed for surge current pulse measurements**
- **Probe is physically isolated from the circuit**
- **Ready to use**
- **No additional attenuators needed**

The MD 300 probe has been specially designed to verify surge current pulses as specified in IEC/EN 61000-4-5, ANSI C62.41 and their derivatives.

The main advantage of the MD 300 current probe is, that the measuring system is physically isolated from the circuit under test.

The MD 300 current probe is ready to use as coming along with pre-mounted coaxial cable. The BNC-end plug needs to be connected to the high-impedance input or 50 Ω input of an ordinary memory oscilloscope. Then the conductor carrying the surge current to be measured is passed through the hole in the current probe. The resulting voltage wave shape on the oscilloscope will then be an authentic reproduction of the actual current wave shape within the given accuracy.

The probe can be used for current pulse verification on surge generators. Optional FISCHER or LEMO connectors are available for matching the safety banana connectors of the shorting cable to the HV output of the generator. For monitoring the EUT current during a test, an additional IEC adaptor with the safety banana connectors can be connected to the generator EUT output for observation of one lead at a time.

MD 300 SURGE PULSE CURRENT PROBE SET

Technical specifications

Maximum peak current	5000 Amp
Maximum RMS current	>63 Amp
Nominal ratio	500:1 (into 1 M Ω system) 1000:1 (into 50 Ω system)
Sensitivity	0.002 V/Amp (1 M Ω system) 0.001 V/Amp (50 Ω system)
Lower frequency (3 dB cut off)	<10 Hz
Higher frequency (3 dB cut off)	>20 MHz
Hole diameter	8 mm
Probe connector	SMA
Scope coax cable	with SMA and BNC connectors
Operating temperature	0 to 55°C
Output impedance	50 Ω
Accuracy	< \pm 2%

MD 300 set

Carry case, Current probe, Coax cable with SMA/BNC connector, Shorting cable with safety banana connectors, Calibration certificate, User manual

Options

INA 3236	FISCHER to banana plug adaptor set
INA 2042	LEMO to banana plug adaptor set
INA 3233	IEC320 single phase to safety banana adaptor leads

Note: The carry case provides spare place for all options.

Teseq AG

Nordstrasse 11F 4542 Luterbach Switzerland
T +41 32 681 40 40 F +41 32 681 40 48
sales@teseq.com www.teseq.com

© June 2015 Teseq®

Specifications subject to change without notice. Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.

691-007B June 2015