


For Tests
acc. to KÖNIG
and PERSOZ



Pendulum Damping Tester Model 299/300

Automatic
Pendulum Excursion

Automatic
Pendulum Alignment



testing equipment for quality management

ERICHSEN

Technical Description

SNV 37 112
SIS 18 41 86
NEN 5319
VDA 621 - 410

DIN 53 157
DIN ISO 1522
ASTM D 4366
NF T 30 016
BS 3900 : E5

Purpose and Application

Pendulum damping tests with the **Pendulum Damping Tester, Model 299/300**, assess the mechanical damping properties of paints, varnishes and similar coatings.

Test Principle

The oscillations of a standardised pendulum placed on the test surface are damped in proportion to the "softness" of the coating.

Design and Function

The stand appliance consists of a support and a base plate with levelling screws. The support holds a specimen holder for test panels measuring up to 250 x 100 x 15 mm. The instrument is protected against dust and draught by an acrylic glass hood which has openings for positioning the specimens. The pendulum damping tester is operated from a control terminal located outside the housing.

As optional accessories two different pendulums with yokes, made of rust-resistant steel, are available:

- ◆ *Pendulum in accordance with König*, conforming to DIN 53 157
- ◆ *Pendulum in accordance with Persoz*, conforming to NF T 30-016

The pendulum is automatically adjusted, avoiding time-consuming fine-setting of the light barrier.

Two different **measuring modules** are available:

• Basic version

The excursion of the pendulum is effected manually by way of a lever mechanism. The pendulum is actuated by way of cable release.

• Automatic version

The excursion and actuation of the pendulum are effected automatically.

The automatic version offers the following additional advantages:

- ◆ user-friendly operation
- ◆ consistent test results
- ◆ simple change of pendulum type

In both versions the pendulum type is entered on the **control terminal**. Readings on the 4-digit LC display show alternatively

- ◆ the number of oscillations
- ◆ the length of test, or
- ◆ the period of oscillation

Reference Class:

Both versions (manual/automatic) of Model 299/300 are supplied with a Manufacturer's Certificate M in accordance with DIN 55 350-18 that includes among others the following information:

Actual and setting values for the oscillation quantities of the pendulum, evenness of the calibrating plate, product identification, test equipments used with calibration status, date, name of inspector.

By means of one calibrated König and Persoz pendulum each the actual values of the number of oscillations, the duration of oscillation as well as the period are determined for the basic instrument and compared with the setting values.

Technical Data

Basic Instrument:

Dimensions: Height: 700 mm
Width: 325 mm
Depth: 345 mm
Net weight: approx. 17 kg

Measuring Module (basic version):

Dimensions: Height: 60 mm
Width: 235 mm
Depth: 70 mm
Net weight: approx. 0.5 kg

Measuring Module (automatic version):

Dimensions: Height: 65 mm
Width: 235 mm
Depth: 107 mm
Net weight: approx. 0.75 kg

Control Terminal:

Dimensions: Height: 35 mm
Width: 167 mm
Depth: 65 mm

Net weight: approx. 0.4 kg

Supply voltage: 230 VAC ± 10 %

Power consumption: 25 VA

Order Information	
Order No.	Product Name
0085.00.31	Pendulum damping tester, Model 299/300 <u>without</u> pendulum and measuring module
Scope of delivery includes: <ul style="list-style-type: none">◆ Protective acrylic glass hood◆ Calibrating plate with Manufacturer's Test Certificate◆ Box level◆ Operating instructions	

Accessories	
Order No.	Product Name
0432.01.32	Pendulum for measurements <i>in acc. with König</i> , incl. case and with Manufacturer's Test Certificate
0432.02.32	Pendulum for measurements <i>in acc. with Persoz</i> , incl. case and with Manufacturer's Test Certificate
0459.01.32	Measuring module for basic version, incl. control terminal (manual pendulum excursion), with Manufacturer's Test Certificate
0460.01.32	Measuring module for automatic version, incl. control terminal (automatic pendulum excursion), with Manufacturer's Test Certificate

Remark:

Older types of pendulum damping tester equipment can also be retrofitted with a new measuring module.

Subject to technical modification.
Group 14 - TBE 299/300 – VIII/2007