

COATING THICKNESS GAUGE

MODEL: TG-03



FEATURES:

LCD display Reverse for easy reading.
For the ferrous material use.
Data logging function capacity up to 255 samples.
Warning beeper triggers by Hi/Lo limit settings.
MAX/MIN/MAX-MIN/AVG function.
Fast one point calibration for frequent measuring thickness use.
2 points calibration for normal use.
 μm /mils user-selective.
Back-Light feature.
Auto Power Off: 30 seconds.
Response Time: 1 second.
Storage Temperature: -4°F to 140°F (-20°C to 60°C), 0 to 80% R.H. with battery removed from meter.
Battery: 1.5V (AAA size) x 2pcs.
Dimensions: 105mm(H) x 55mm(W) x 27mm(D).
Weight: Approx. 80g(including battery).

SPECIFICATIONS

Operating Environment: 32°F to 122°F (0°C to 50°C) at $<75\%$ R.H.

Thickness Range: 0 to 80.0mils, 0 to 2000 μm .

Display Resolution: 0.1mils/1 μm .

Accuracy:

± 4 dgts on 0 to 7.8mils

$\pm(3\%+4$ dgts) on 7.9mils to 39.0mils

$\pm(5\%+4$ dgts) on 39.1mils to 80.0mils

± 10 dgts on 0 to 199 μm

$\pm(3\%+10$ dgts) on 200 μm to 1000 μm

$\pm(5\%+10$ dgts) on 1001 μm to 2000 μm

Accuracy: Stated accuracy at $23^{\circ}\text{C}\pm 5^{\circ}\text{C}$, $<75\%$ R.H.

Temperature Coefficient: 0.1x (specified accuracy)/ $^{\circ}\text{C}$ ($<18^{\circ}\text{C}$ or $> 28^{\circ}\text{C}$)

CHY FIREMATE CO., LTD.

NO.3, SHENGLI 1ST ST., XINTIAN VILLAGE,
RENDE DISTRICT, TAINAN CITY, TAIWAN R.O.C.
TEL: 886-6-2794811 FAX: 886-6-2700227
E-mail: chy@chy-meter.com