## Technical Data Snow Depth Sensor SHM31





The laser-based snow depth sensor Lufft SHM31 stands for millimeteraccurate snow level detection over long distances in all weather conditions without any maintenance, due to opto-electronic/laser based rangefinder technology.

- Parameters measured
   Snow depth
- Measurement technology
   opto-electronic measuring technique (rangefinder; laser distance sensor) with eye safe laser
- Product highlights

Determination of snow depth over long distances, heating options allow high quality measurements in all weather conditions, simplified installation due to automatic inclination angle compensation

- Interfaces
   RS485 & RS232 with UMB, UMB-ASCII 2.0 & SDI12 protocol
- Article number 8365.30

Millimeter-accurate snow levels in all weather conditions: The SHM 31 operates with a visible, easy-to-measure measuring beam. The snow depth is given up to 15 meters within seconds, millimeter-accurate and reliable. Various heating functions significantly extend the lifetime of the laser diode and allow high-quality measurement data in all weather conditions. Regular maintenance becomes redundant with the SHM 31. A very robust









## **Technical Data**Snow Depth Sensor SHM31



housing and an elaborate operation principle allows almost no maintenance work throughout the lifetime of the sensor.

General	
Dimensions (LxWxH)	302mm × 130mm × 234mm
Weight	2,35 kg
Operating parameters	
Temperature range	-40°C+50 °C
Relative humidity	0%100%

Measuring parameters		
Snow Depth	0 15 m	
Mounting distance to surface	0,1 16 m	
Accuracy (snow depth)2	± (5 mm + 0.06 %)	
Repeatability	0.6 mm	
Intermediate precision/	5 mm	
reproducibility		

Data-interfaces	
RS485	ASCII, UMB protocol
RS232	ASCII protocol
SDI-12	SDI-12 protocol
Data transfer mode	Polling (UMB, ASCII, SDI-12); Auto telegram output (ASCII)

Electrical parameters		
typ. power consumption at 24	without heater: approx. 0.7 W; with window heating: approx. 3.4	
Vdc and 10 s laser measurement	W	
interval		
Power supply	12, 24 VDC	
Maximum power	18 W	
consumption(connecting power		
with heater on)		

Safety	
Laser classification	Laser class 2 (IEC 60825-1:2014)
Protection class	IP68
EMC	EN 61326-1:2012 (industrial standard)
EC	2014/30/EU & RoHS 2011/65/EU



